

# G2 Bean Builder

User's Guide

Version 2020



G2 Bean Builder User's Guide, Version 2020

June 2020

The information in this publication is subject to change without notice and does not represent a commitment by Gensym Corporation.

Although this software has been extensively tested, Gensym cannot guarantee error-free performance in all applications. Accordingly, use of the software is at the customer's sole risk.

Copyright © 1985-2020 Gensym Corporation

All rights reserved. No part of this document may be reproduced, stored in a retrieval system, translated, or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of Gensym Corporation.

Gensym®, G2®, Optegrity®, and ReThink® are registered trademarks of Gensym Corporation.

NeurOn-Line™, Dynamic Scheduling™, G2 Real-Time Expert System™, G2 ActiveXLink™, G2 BeanBuilder™, G2 CORBALink™, G2 Diagnostic Assistant™, G2 Gateway™, G2 GUIDE™, G2GL™, G2 JavaLink™, G2 ProTools™, GDA™, GFI™, GSI™, ICP™, Integrity™, and SymCure™ are trademarks of Gensym Corporation.

Telewindows is a trademark or registered trademark of Microsoft Corporation in the United States and/or other countries. Telewindows is used by Gensym Corporation under license from owner.

This software is based in part on the work of the Independent JPEG Group.

Copyright © 1998-2002 Daniel Veillard. All Rights Reserved.

SCOR® is a registered trademark of PRTM.

License for Scintilla and SciTE, Copyright 1998-2003 by Neil Hodgson, All Rights Reserved.

This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit (<http://www.openssl.org/>).

All other products or services mentioned in this document are identified by the trademarks or service marks of their respective companies or organizations, and Gensym Corporation disclaims any responsibility for specifying which marks are owned by which companies or organizations.

Ignite Technologies, Inc.  
401 Congress Ave., Suite 2650  
Austin, TX 78701 USA  
Telephone: +1-800-248-0027  
Email: [success@ignitetech.com](mailto:success@ignitetech.com)

Part Number: DOC056-1200

# Contents

---

	<b>Preface</b>	<b>vii</b>
	About this Guide	vii
	Software Requirements	vii
	Audience	vii
	Conventions	viii
	Related Documentation	ix
	Customer Support Services	xii
<b>Chapter 1</b>	<b>Introduction</b>	<b>1</b>
	Introduction	1
	Java Beans	2
	G2 Java Beans	2
	Differences between G2 and Java	3
	Inheritance Model	3
	Accessing Attributes	3
	Events	4
<b>Chapter 2</b>	<b>Installing the G2 Bean Builder</b>	<b>5</b>
	Introduction	5
	Software Requirements	5
	Installing the Files	6
	Checking the Installation	6
	Minimum Requirement for Distributing Java Beans	6
	File Locations	6
	Troubleshooting	7
	Running the Beans Development Kit (BDK)	7
	Using the ActiveX Packager	8
<b>Chapter 3</b>	<b>Running the Wizard</b>	<b>11</b>
	Introduction	11

Running the G2 Bean Builder	12
Viewing the Welcome Panel	13
Configuring the G2 Connection Details	14
Specifying the Host	15
Specifying the Port	15
Configuring the G2 Class Name	16
Entering the G2 Class	17
Forcing an Interface Download	17
Configuring the Iconic Representation	18
Entering the File Name	19
Using the G2 Icon for the Bean	19
Configuring the JAR File	20
Entering the Directory and File Name	20
ActiveX Generation Panel	21
Creating an ActiveX Component from the Bean	22
Unregistering Existing Class	22
Summary Panel	23
Progress of Bean Building Panel	24
Connecting to G2	25
Downloading Class Data	25
Building the Bean	25
Jar File Creation	25
Building the ActiveX Control	25
Finished Panel	26

## **Chapter 4 Using the Command-Line Options 29**

Introduction	30
-host	30
-port	31
-class	31
-force	32
-iconfile	32
-notg2icon	32
-dir	33
-jarfile	33
-activex	33

-unreg 34

+g 34

+t 34

+v 34

## **Chapter 5 Using G2 Bean Builder Beans 35**

Introduction 35

Creating the G2 Class 36

Creating the Bean 36

Using the Bean in the Beans Development Kit (BDK) 37

Viewing the Bean in the Bean Box 39

Creating an Instance of the Bean 41

Configuring the Bean 42

Interacting with Other Beans 46

Using the Bean as an ActiveX Control in Visual Basic 48

Importing Beans into Visual Basic 48

Creating an Instance of the ActiveX Control 49

**Index 53**



# Preface

---

*Describes this guide and the conventions that it uses.*

About this Guide	vii
Software Requirements	vii
Audience	vii
A Note About the API	viii
Conventions	viii
Related Documentation	x
Customer Support Services	xi



## About this Guide

This guide describes the basic features of G2 Bean Builder and explains how you can use these features to create applications.

## Software Requirements

For information about the software requirements and installation of this version of G2 Bean Builder, refer to the `readme.html` file supplied with G2 JavaLink, which includes this and other important instructions.

## Audience

This document assumes that you are familiar with the features and syntax of the Java programming language, and that you know how to develop Java applications. It also assumes that you are familiar with the syntax of G2.

# Conventions

This guide uses the following typographic conventions and conventions for defining system procedures.

## Typographic

Convention Examples	Description
g2-window, g2-window-1, ws-top-level, sys-mod	User-defined and system-defined G2 class names, instance names, workspace names, and module names
history-keeping-spec, temperature	User-defined and system-defined G2 attribute names
true, 1.234, ok, "Burlington, MA"	G2 attribute values and values specified or viewed through dialogs
Main Menu > Start KB Workspace > New Object create subworkspace Start Procedure	G2 menu choices and button labels
conclude that the x of y ...	Text of G2 procedures, methods, functions, formulas, and expressions
<i>new-argument</i>	User-specified values in syntax descriptions
<u>text-string</u>	Return values of G2 procedures and methods in syntax descriptions
File Name, OK, Apply, Cancel, General, Edit Scroll Area	GUIDE and native dialog fields, button labels, tabs, and titles
File > Save Properties	GMS and native menu choices
<b>workspace</b>	Glossary terms

Convention Examples	Description
c:\Program Files\Gensym\ /usr/gensym/g2/kbs	Windows pathnames UNIX pathnames
spreadsh.kb	File names
g2 -kb top.kb	Operating system commands
public void main() gsi_start	Java, C and all other external code

**Note** Syntax conventions are fully described in the *G2 Reference Manual*.

## Procedure Signatures

A procedure signature is a complete syntactic summary of a procedure or method. A procedure signature shows values supplied by the user in *italics*, and the value (if any) returned by the procedure underlined. Each value is followed by its type:

```
g2-clone-and-transfer-objects
  (list: class item-list, to-workspace: class kb-workspace,
   delta-x: integer, delta-y: integer)
  -> transferred-items: g2-list
```

## Related Documentation

### G2 Core Technology

- *G2 Bundle Release Notes*
- *Getting Started with G2 Tutorials*
- *G2 Reference Manual*
- *G2 Language Reference Card*
- *G2 Developer's Guide*
- *G2 System Procedures Reference Manual*

- *G2 System Procedures Reference Card*
- *G2 Class Reference Manual*
- *Telewindows User's Guide*
- *G2 Gateway Bridge Developer's Guide*

## **G2 Utilities**

- *G2 ProTools User's Guide*
- *G2 Foundation Resources User's Guide*
- *G2 Menu System User's Guide*
- *G2 XL Spreadsheet User's Guide*
- *G2 Dynamic Displays User's Guide*
- *G2 Developer's Interface User's Guide*
- *G2 OnLine Documentation Developer's Guide*
- *G2 OnLine Documentation User's Guide*
- *G2 GUIDE User's Guide*
- *G2 GUIDE/UII Procedures Reference Manual*

## **G2 Developers' Utilities**

- *Business Process Management System Users' Guide*
- *Business Rules Management System User's Guide*
- *G2 Reporting Engine User's Guide*
- *G2 Web User's Guide*
- *G2 Event and Data Processing User's Guide*
- *G2 Run-Time Library User's Guide*
- *G2 Event Manager User's Guide*
- *G2 Dialog Utility User's Guide*
- *G2 Data Source Manager User's Guide*
- *G2 Data Point Manager User's Guide*
- *G2 Engineering Unit Conversion User's Guide*
- *G2 Error Handling Foundation User's Guide*
- *G2 Relation Browser User's Guide*

## **Bridges and External Systems**

- *G2 ActiveXLink User's Guide*
- *G2 CORBALink User's Guide*
- *G2 Database Bridge User's Guide*
- *G2-ODBC Bridge Release Notes*
- *G2-Oracle Bridge Release Notes*
- *G2-Sybase Bridge Release Notes*
- *G2 JMail Bridge User's Guide*
- *G2 Java Socket Manager User's Guide*
- *G2 JMSLink User's Guide*
- *G2 OPCLink User's Guide*
- *G2 PI Bridge User's Guide*
- *G2-SNMP Bridge User's Guide*
- *G2 CORBALink User's Guide*
- *G2 WebLink User's Guide*

## **G2 JavaLink**

- *G2 JavaLink User's Guide*
- *G2 DownloadInterfaces User's Guide*
- *G2 Bean Builder User's Guide*

## **G2 Diagnostic Assistant**

- *GDA User's Guide*
- *GDA Reference Manual*
- *GDA API Reference*

# Customer Support Services

You can obtain help with this or any Gensym product from Gensym Customer Support. Help is available online, by telephone and by email.

## To obtain customer support online:

➔ Access Ignite Support Portal at <https://support.ignitetechnology.com>.

You will be asked to log in to an existing account or create a new account if necessary. Ignite Support Portal allows you to:

- Register your question with Customer Support by creating an Issue.
- Query, link to, and review existing issues.
- Share issues with other users in your group.
- Query for Bugs, Suggestions, and Resolutions.

## To obtain customer support by telephone or email:

➔ Use the following numbers and addresses:

**United States Toll-Free** +1-855-453-8174

**United States Toll** +1-512-861-2859

**Email** [support@ignitetechnology.com](mailto:support@ignitetechnology.com)

# Introduction

---

*Introduces the G2 Bean Builder.*

Introduction	1
Java Beans	2
G2 Java Beans	2
Differences between G2 and Java	3



## Introduction

The G2 Bean Builder is a Java-based wizard that uses G2 JavaLink to create a Java Bean from a G2 class.

You use the G2 Bean Builder to build a Java Bean in its own JAR file by either:

- Providing the data through the wizard.
- Entering the data as command-line options.

Please refer to the *G2 JavaLink User's Guide* for further in-depth information on G2-Java communication and the mapping of G2 types and classes to Java.

On the Windows platform, the G2 Bean Builder can package Java Beans as ActiveX controls for use with third-party ActiveX development environments, such as Visual Basic. Note that platform restrictions may apply.

This feature uses an ActiveX packager from Sun Microsystems that creates OLE type library information and win32 registry information for a selected Java Bean, which allows OLE/COM containers to correctly analyze and present a Bean. For

example, a Bean's properties are correctly presented in a Visual Basic property sheet.

The two sources of the ActiveX packager available from Sun Microsystems are:

- Java Bean to ActiveX Bridge
- Java Plug-in

Previous versions of the G2 Bean Builder have used the packager distributed with Sun Microsystems' Java Bean to ActiveX Bridge. However, the G2 Bean Builder now uses the packager included with Sun's Java Plug-in, which is included with JDK.

## Java Beans

A Java Bean is:

*"... a reusable platform-neutral software component that can be visually manipulated in a software development tool "- Java Beans Specification 1.0*

Java Bean components are called Beans. Beans may be thought of as segments of code, which, in addition to their designed function, can also "plug-and-play" with other Beans.

Adopting Beans as the unit of software allows the Bean developer to create the basic functional units. The user then assembles these units, using a visual Bean-editing environment to create the final application.

## G2 Java Beans

A G2 Java Bean/ ActiveX control created by the G2 Bean Builder for a specific G2 class is a reusable visual component that you can use within a Java Beans- or ActiveX-compliant development environment. The resulting Bean also exposes the interfaces of the original G2 class so that third-party development environments such as Visual Basic or Visual Café can present methods and attributes of the original G2 class at development time. For the Bean to be useful, it must be configured to access an instance of the original G2 class within a G2 server running on the network.

Once the Bean is connected to a G2 object:

- Its attribute values are synchronized with the current values of the G2 object.
- Any changes to attributes made to the Bean are reflected as attribute changes on the G2 object.
- Any changes to attributes made to the G2 object are reflected as attribute changes on the Bean.

- Any method that is exported from the original G2 class and called on the Bean results in a synchronous method call on the appropriate G2 method. Any G2 type or class can be returned from a G2 method call to the Bean.

---

**Note** Any events defined on the G2 object are also reported to the Bean. Exposed events must be defined by using the G2 Event Listener Support Module. For more information, see the *G2 JavaLink User's Guide*.

---

- If Gensym's Telewindows2 Toolkit is installed and the bean has been configured to use the G2 icon, then the generated Bean displays the current icon of the connected G2 object.

## Differences between G2 and Java

There are differences as well as similarities between Java and G2. The following sections describe a number of these differences and how to overcome them.

### Inheritance Model

The Java class inheritance model does not support multiple inheritance, whereas G2 does. To circumvent this difference, G2 JavaLink maps G2 classes to Java interfaces, which do support multiple inheritance. JavaLink creates Java *implementation* classes from the original G2 class to implement multiple interfaces, thereby mapping G2's multiple inheritance in the Java environment.

### Accessing Attributes

Using Java Beans, you obtain attribute values by using methods known as getters, and you modify attributes by using methods known as setters.

For example, suppose you have a G2 class named `tank` with a `temperature` attribute. The resulting Bean would have a getter called `getTemperature`, which returns the `temperature` attribute value for a given `tank`, whose definition would look like this:

```
public int getTemperature() {
    return temperature;
}
```

For example, you could use this getter like this:

```
if (tank1.getTemperature() > 10) . . . .
```

You use a similar mechanism for setting the value of the attribute like this:

```
public void setTemperature(int temp){
    if((temp > 0) && (temp < 100)){
        temperture = temp;
    }else ...
}
```

Notice that the setter performs bounds checking for the attribute. That way, all the calling code has to be concerned with is setting the attribute value; the setter takes care of error checking and so on.

## Events

An event is an asynchronous signal that a source object sends to a target object to notify the target that some specific behavior has occurred.

In the Java event model, a “source” can send a single event to any number of “listeners.” A source is an object that generates events, and a Listener is an object that implements the appropriate listener interface so it can receive events. Sources implement standard methods so that listeners can request notification of events. After a listener registers with a source, it gets called any time an event of the requested type occurs.

For example, when an attribute value of a G2 object changes, the `propertyChangeEvent` is generated for all objects that implement the `ItemListener` interface.

To export events to external Java Beans or ActiveX controls, you must use the G2 Event Listener Support Module (`g2evlis.kb`), as described in the *G2 JavaLink User's Guide*.

# Installing the G2 Bean Builder

---

*Describes installation and distribution of the G2 Bean Builder.*

Introduction	5
Software Requirements	5
Installing the Files	6
Checking the Installation	6
Minimum Requirement for Distributing Java Beans	6
Troubleshooting	7



## Introduction

This chapter describes how to check the installation of the G2 Bean Builder and troubleshoot the installation. It also describes what you need to do when distributing Java Beans and ActiveX controls that the G2 Bean Builder has created.

## Software Requirements

For information about the software requirements for this version of G2 Bean Builder, see the `readme-javalink.html` file supplied with G2 JavaLink.

## Installing the Files

For information about installation, refer to the `readme-javalink.html` file, supplied with G2 JavaLink, which includes installation and other important instructions.

## Checking the Installation

To verify the G2 Bean Builder installation, enter the following command on a command line:

```
java com.gensym.beanbuilder.G2BeanBuilder +v
```

This command provides a simple though not exhaustive self-test facility. The application should display a message that shows the result of the self test and the version of G2 Bean Builder. For example:

```
Gensym G2 Bean Builder Version 1.2 Rev. 5  
Self Test Passed
```

## Minimum Requirement for Distributing Java Beans

When you distribute a packaged Java Bean that you created with the G2 Bean Builder, the following requirement must be met for the packaged Java Bean to work:

Java Development Kit (JDK) 1.3, which includes the Java Plug-in 1.3, or Java Runtime Environment (JRE) 1.3.

---

**Note** For the latest software requirements, see the `readme-javalink.html` file included with G2 JavaLink.

---

## File Locations

The G2 Bean Builder uses the property named `com.gensym.class.user.repository`, which is defined in the JavaLink properties file `.com.gensym.properties`, to indicate where to create JAR files.

For example, the property might be defined as follows, where `g2-install-dir` is your G2 installation directory:

```
com.gensym.class.user.repository=g2-install-dir\javalink\classes
```

When the G2 Bean Builder creates the JAR file, it appends `\jars` to the specified path and uses the resulting path as the destination directory for its JAR files. In the example above, it would create JAR files in this directory of your G2 installation directory:

```
\javalink\classes\jars
```

You can also specify the JAR file location by using the:

- G2 Bean Builder Dir type-in box.
- `-dir` command-line option.

If you use either of these options, the G2 Bean Builder creates JAR files in the specified directory.

The G2 Bean Builder automatically creates ActiveX controls in the `activex` directory within the JAR directory, for example:

```
\javalink\classes\jars\activex
```

In order for the ActiveX components to function in environments such as Visual Basic, you must copy the `beans.ocx` file located in the `JavaPlugin\bin` directory to this `activex` directory.

For further information about the properties file and the JavaLink file location, see the *G2 JavaLink User's Guide*.

## Troubleshooting

This section provides help troubleshooting the installation.

### Running the Beans Development Kit (BDK)

You use Sun's Beans Development Kit (BDK) V1.1 to test Java Beans created from G2 Bean Builder. You run BDK from the following batch file:

```
../BDK/beanbox/run.bat
```

The batch files look like this on each platform:

- Windows:

```
if "%OS%" == "Windows_NT" setlocal
set CLASSPATH=classes;..\lib\methodtracer.jar;..\infobus.jar
java sun.beanbox.BeanBoxFrame
```

- UNIX:

```
#!/bin/sh
export CLASSPATH
CLASSPATH=classes
java sun.beanbox.BeanBoxFrame
```

Unfortunately, the batch file overrides the CLASSPATH so that JavaLink classes are not visible to the Bean Box application. Assuming you attempt to load ATestClassBean from C:\bt\mg\java\jars\ATestClassBean.jar, the Bean Box prints in its console window the following exception message:

```
WARNING: Could not instantiate bean "com.gensym.classes.modules.
jgidemo.ATestClassBean" from JAR "C:\bt\mg\java\jars\ATestClassBean.
jar" BeanBox caught exception java.lang.SecurityException: No access
through getResource() to .class in 1.1 while processing: LoadJar msg:
No access through getResource() to .class in 1.1
```

You can resolve this problem by editing the run.bat file to ensure that all required JavaLink classes are on the Bean Box's CLASSPATH. Because the JavaLink installation ensures that the default CLASSPATH points to the correct JavaLink classes, the following change to line 2 normally solves the problem:

- Windows:

```
if "%OS%" == "Windows_NT" setlocal
set CLASSPATH=%CLASSPATH%;classes..\lib\methodtracer.jar;
..\infobus.jar
java sun.beanbox.BeanBoxFrame
```

- UNIX:

```
#!/bin/sh
export CLASSPATH
CLASSPATH=$CLASSPATH;classes
java sun.beanbox.BeanBoxFrame
```

## Using the ActiveX Packager

The G2 Bean Builder uses the packager supplied with Sun's Java Plug-in to create ActiveX controls from Java Beans that have been created for G2 objects. When the G2 Bean Builder starts up, it searches for the ActiveX Packager Java startup class, sun.beans.ole.Packager, from the current CLASSPATH. If the Packager cannot be found, the G2 Bean Builder does not give the user the option of creating an ActiveX control. To ensure the Packager can be found, you should install it correctly along with Sun's Bean Development Kit.

This release of JavaLink uses the packager supplied with Sun's Java Plug-in 1.3, which is included with JDK 1.3.

To ensure that the G2 Bean Builder can find the Packager, you need to add the Java Plug-in's Java classes directory to the CLASSPATH as follows, assuming the Java Plug-in has been installed at c:\Program Files\JavaSoft\JRE\1.3:

```
set CLASSPATH=%CLASSPATH%;c:\Program Files\JavaSoft\JRE
\1.3\lib\jaws.jar
```

In addition, you need to add the Java Plug-in's Java bin directory to the PATH as follows:

```
set PATH=%PATH%;c:\Program Files\JavaSoft\JRE\1.3\bin
```

The G2 Bean Builder places ActiveX registration (.reg) and type library (.tlb) files generated for the G2 Bean in a directory called `activex`, which is automatically created below the Java Bean JAR directory specified while building the Bean.

For example, assume the JAR is generated in this directory of your G2 installation directory:

```
\javalink\classes\jars
```

The ActiveX control files would be created in:

```
\javalink\classes\jars\activex
```

### Packager Notes

- The registration file created contains absolute references to the location of the Java Bean JAR and other files. If you move any of these files, you must edit the registration file appropriately. To edit a .reg file entered into the Windows registry, double-click the file from a file view or use `regedit` from a DOS prompt.
- If you use the Packager to re-create the same ActiveX control, the .reg and .tlb files are overwritten. Any edits you have made to these files must be reentered.
- If an ActiveX control is previously registered and you rerun the Packager to re-create the same ActiveX Control, the Packager maintains the same GUID for the ActiveX control.
- The Packager uses a common control file called `beans.ocx` that is normally placed in `c:\Program Files\JavaSoft\JRE\1.3\bin`, assuming the Packager is installed in `c:\Program Files\JavaSoft\JRE\1.3\bin`. You must copy this file to any `activex` directory that the G2 Bean Builder creates, or the generated ActiveX controls will not work. For example, if `beans.ocx` is not found, Visual Basic would report that the generated G2 ActiveX Bean control has not been registered, when a user attempts to draw the control on a VB form.
- When switching to a new version of the Packager, you must re-create your G2 beans, using the G2 Bean Builder. If you have copies of the `beans.ocx` file from the previous version of the Packager, you must replace these with the newer version of the `beans.ocx` file supplied with Sun's Plug-in, which is found in the `\bin` directory in the Plug-in's installation directory.



# Running the Wizard

---

*Describes how to use the G2 Bean Builder wizard.*

Introduction	11
Running the G2 Bean Builder	12
Viewing the Welcome Panel	13
Configuring the G2 Connection Details	14
Configuring the G2 Class Name	16
Configuring the Iconic Representation	18
Configuring the JAR File	20
ActiveX Generation Panel	21
Summary Panel	23
Progress of Bean Building Panel	24
Finished Panel	26



## Introduction

You use the G2 Bean Builder utility by running a wizard, which provides a graphical user interface (GUI) to the utility. Alternatively, you can run the utility without the wizard.

# Running the G2 Bean Builder

Before running the G2 Bean Builder, you must:

- Launch G2.
- Load the KB containing the classes for which you require Java interfaces.

You can run the G2 Bean Builder with or without a graphical user interface.

## To run the G2 Bean Builder with a GUI:

➔ From a command window, execute this command:

```
java com.gensym.beanbuilder.G2BeanBuilder
```

or

➔ Launch the utility from the Start menu, by choosing the following from your Gensym G2 program group:

G2 JavaLink > G2 Bean Builder

## To run G2 Bean Builder without a GUI:

➔ From a command window, execute this command:

```
java com.gensym.beanbuilder.G2DownloadInterfaces  
-class MY-CLASS
```


This command runs G2 DownloadInterfaces on MY-CLASS without a GUI.

The remaining instructions assume you have started the G2 Bean Builder with a GUI.

For information on running the G2 Bean Builder without a GUI, see [Using the Command-Line Options](#).

## Viewing the Welcome Panel

Once you start the G2 Bean Builder, the Welcome panel appears:



This panel displays the version of G2 Bean Builder currently running and provides these buttons:

Clicking this button:	Does this:
About	Displays the About screen that shows the current version of G2 JavaLink.
Back	Displays the previous panel. This button is initially inactive, because the Welcome panel is the first panel.
Next	Displays the next panel. Some panels cause this button to be inactive until you enter all of the information on that panel.


Clicking this button:	Does this:
Restart	Aborts the current build and restarts the session.
Exit	Presents a confirmation dialog asking you to confirm exiting from the G2 Bean Builder.

The four navigation buttons and the Help button are common to all of the G2 Bean Builder panels.

Click Next to advance to the G2 Connection Details panel.

## Configuring the G2 Connection Details

The G2 Connection Details panel configures the connection between the G2 Bean Builder and a G2 host:



This panel has two specific controls:

- Host field
- Port field

Configure the Host and Port, then click Next to advance to the G2 Class Name panel.

## Specifying the Host

The Host field holds the name or IP address of the machine running the target G2.

By default, the default Host is `localhost`, unless you started the G2 Bean Builder with the `-host` command-line option, as described in [Using the Command-Line Options](#).


## Specifying the Port

The Port field holds the TCP/IP port number at which G2 is running on the target machine.

By default, the default Port is 1111, unless you started the G2 Bean Builder with the `-port` command-line option, as described in [Using the Command-Line Options](#).

# Configuring the G2 Class Name

The G2 Class Name panel lets you specify the G2 class for which to create a Java Bean:



This panel contains two specific controls:

- Class field
- Force download checkbox

Configure these controls, then click Next to advance to the Iconic Representation panel.

## Entering the G2 Class

The Class field holds the G2 class for which you want to build a Java Bean. When entering the G2 class through the GUI, case does not matter but you must use hyphens if they appear in the G2 class name.

By default, the Class field is blank, unless you started the G2 Bean Builder with the `-class` command-line option, as described in [Using the Command-Line Options](#).

The Next button is disabled unless this field has a value.

## Forcing an Interface Download

The force download checkbox allows interfaces to be created during development so that they pre-exist at deployment time. You should use this option when a G2 class or its methods have changed in some way. Forcing the download guarantees that the Java interface classes are up-to-date.


When the option is not checked, JavaLink only creates the interfaces that it requires, reusing any that were previously downloaded.

You use this feature when using the G2 Bean Builder to “repackage” previously packaged G2 classes, perhaps for creating a JAR file with a new file name or for changing the graphics of the icon.

By default, the force download checkbox is true. You can disable the force download option by unchecking the checkbox.

# Configuring the Iconic Representation

The Iconic Representation panel allows you to select an image to use as the iconic representation for the Bean:



Typically, a Java Bean has associated with it 4 icon files, one each of size 16x16 and 32x32 pixels, both in monochrome and in color. These files are stored within the JAR file. The Bean's `beaninfo` file returns the relevant icon when prompted.

By contrast, the G2 Bean Builder stores one 32x32 image as raw data within the `beaninfo` file. You can use a wide range of graphics file types to specify this image. The source graphics file need not be 32x32, because the G2 Bean Builder automatically scales and stores the image at this resolution. The IDE automatically dithers monochrome images, so there is no need to explicitly store them.

This panel has two specific controls:

- File name field
- Use G2 icon for bean checkbox

Configure these controls, then click the Next button to advance to the Bean Build Information panel.

## Entering the File Name

The File name field holds the name of a valid graphics file from which to create an icon for the Bean.

By default, the File name field defaults to `I32.gif`, which is located in the `images` directory of the G2 Bean Builder product directory. If you started the G2 Bean Builder with the `-iconfile` command-line option, as described in [Using the Command-Line Options](#), the File name field defaults to the file name you specified in the command-line argument.

To specify a new file name, click the button next to the field to display a file dialog from which to choose the source image for the Bean's icon.

The File name field is disabled if the Use G2 icon for bean checkbox is true.


## Using the G2 Icon for the Bean

The Use G2 icon for bean checkbox, when checked, causes the G2 Bean Builder to use the G2 icon of the specified class as the image for the Bean. The image is automatically rescaled.

By default, this checkbox is true, unless you started the G2 Bean Builder with the `-notg2icon` command-line option, as described in [Using the Command-Line Options](#).

# Configuring the JAR File

The Bean Build Information panel allows you to specify the name and location of the JAR file to create:



Configure the JAR file name and directory, then click the Next button to advance to the next panel. Clicking Next displays one of two panels:

- When running on a Windows platform with Sun's Java Plug-in installed, clicking the Next button advances to the ActiveX generation panel.
- Otherwise, clicking the Next button advances to the Summary panel.

## Entering the Directory and File Name

The Dir field holds the name and location of the JAR file to create.

The path component of this field defaults to the path indicated by the value of the `com.gensym.class.user.repository` property with `\jars` appended. This property is defined in the JavaLink properties file, `.com.gensym.properties`. If you started the G2 Bean Builder with the `-dir` command-line option, as described


in [Using the Command-Line Options](#), the path component of the Dir field defaults to the JAR file directory you specified in the command-line option.

The file name component of this field defaults to the name of the G2 class with Bean.jar appended to the name. If you specified the `-jarfile` command-line option, the file name component of the Dir field defaults to the file name you specified in the command-line option.

To specify a new file name, click the button next to the text field to display a file dialog from which to choose the directory location of the JAR file to create.

## ActiveX Generation Panel

The Active X Generation panel allows you to generate an ActiveX control from the Bean, in addition to creating the JAR file:



This panel has two specific controls:

- Create ActiveX component from the bean? checkbox
- Unreg existing class checkbox

Configure these options, then click the Next button to advance to the Summary panel.

## Creating an ActiveX Component from the Bean

This checkbox, if checked, causes the G2 Bean Builder to generate an ActiveX component from the Bean.

This option defaults to false, unless you started the G2 Bean Builder with the `-activex` command-line option, as described in [Using the Command-Line Options](#).

## Unregistering Existing Class

This checkbox, if checked, determines how the G2 Bean Builder deals with the existence of duplicate ActiveX controls:


- If an ActiveX component of the same name as currently registered exists, then the G2 Bean Builder unregisters it first.
- If an ActiveX component of the same name has been registered previously, Sun's ActiveX Packager uses the existing GUID of the previous registration.

For the location of the ActiveX files, see [Installing the G2 Bean Builder](#).

This option defaults to false, unless you started the G2 Bean Builder with the `-unreg` command-line option, as described in [Using the Command-Line Options](#).

## Summary Panel

The Summary panel displays all of the values you entered in each of the previous panels:



At this point, you do not need to configure any more information for the utility to begin building the requested Java Bean. To change any of the values you entered, click Back.

Clicking the Back button at this panel returns to one of two previous panels:

- If the GUI is being run on a Windows platform with Sun's Java Plug-in installed, clicking Back returns to the ActiveX Generation panel.
- Otherwise, clicking the Back button returns to the Bean Build Information panel.

Verify the current settings, then click Next to advance to the Progress of Bean Building panel where the G2 Bean Builder immediately starts creating the Bean.

---

**Note** The summary information pertaining to ActiveX is only visible if the G2 Bean Builder is running on a Windows platform with Sun's Java Plug-in installed and you selected the option to create an ActiveX component on the ActiveX Generation panel.

---

## Progress of Bean Building Panel

The Progress of Bean Building panel displays progress as the bean is created:



This panel has the following specific controls, which indicate the progress of each stage of building the Bean:

- Connecting to G2
- Downloading Class data
- Building bean
- Jar File Creation
- Building Active X control

As each stage begins, the color of the checkbox label changes and the status bar at the bottom updates. As each stage is completed, the color changes again and the checkbox representing that stage is checked, if it completed successfully. The example above indicates that the G2 Bean Builder successfully connected to G2 and that it is currently downloading class data, as indicated by the marker.

During the bean building process, both the Back and Next navigation buttons are disabled.

When the download process is complete, the system automatically advances to the Finished panel.

## Connecting to G2

During this stage, the G2 Bean Builder attempts to establish a connection with the specified G2. If the connection attempt fails, the error is reported to the wizard and no further building takes place.

## Downloading Class Data

Once a connection has been established, the G2 Bean Builder attempts to extract information regarding the target G2 class.

If the specified class is not found, the application informs the user and downloading stops. Otherwise, all of the relevant data is obtained from the target G2 for G2 Bean Builder to complete its task.

## Building the Bean

During this stage, the G2 Bean Builder creates and compiles a number of Java files to create the Bean. When the Bean is used in an IDE, the object has an appearance. The G2 Bean Builder either automatically extracts the G2 iconic representation for the object class and uses it for the Java Beans representation or uses the specified icon. You can see a preview of the Bean's icon in the icon preview next to the checkbox associated with this stage.

## Jar File Creation

During this stage, the G2 Bean Builder creates all the relevant files and places them in a JAR file.

## Building the ActiveX Control

During this phase, the G2 Bean Builder creates an ActiveX control from the Bean. This process leaves the Bean untouched; however, it adds a number of OLE Java bridge files to the JAR file.

This phase places the .reg and .tlb files in the following location:

*jar-directory\activex*

For example:

*g2-install-dir\javalink\classes\jars\activex*


---

**Note** The creation of an ActiveX control is only visible if the G2 Bean Builder is running on an Windows platform with Sun's Java Plug-in installed and you selected the option to create an ActiveX component on the ActiveX Generation panel.

---

## Finished Panel

The Finished panel displays a report of the build, detailing the results of the build:



---

**Note** The result of making an ActiveX Component is only visible if the G2 Bean Builder is running on a Windows platform with Sun's Java Plug-in installed and you selected the option to create an ActiveX component on the ActiveX Generation panel.

---



# Using the Command-Line Options

---

*Describes how to use the G2 Bean Builder wizard.*

Introduction 30

-host 30

-port 31

-class 31

-force 32

-iconfile 32

-notg2icon 32

-dir 33

-jarfile 33

-activex 33

-unreg 34

+g 34

+t 34

+v 34



# Introduction

You can start the G2 Bean Builder by using one or more of the following command-line options:

- -host
- -port
- -class
- -force
- -iconfile
- -notg2icon
- -dir
- -jarfile
- -activex
- -unreg
- +g
- +t
- +v

## -host

Specifies the name or IP address of the machine on which the target G2 is running. If you do not use this command-line option, the utility uses `localhost` as the default value.

**To use the -host option:**

```
➔ java com.gensym.beanbuilder.G2BeanBuilder  
    -host [machine-name | IP-address]
```

where *machine-name* and *IP-address* can be a machine name or an IP address. For example:

```
java com.gensym.beanbuilder.G2BeanBuilder  
    -host mc1
```

or

```
java com.gensym.beanbuilder.G2DownloadInterfaces  
    -host 1.2.3.4
```

If you use this command-line option when using the wizard, then the host you enter appears automatically in the G2 Connection Details panel, as described in [Specifying the Host](#).

## -port

Specifies the port number of the machine on which the G2 process is running. If you do not use this command-line option, the utility uses port 1111 as the default value.

### To use the `-port` option:

```
→ java com.gensym.beanbuilder.G2BeanBuilder
    -port port-number
```

where *port-number* is the G2 port number. For example:

```
java com.gensym.beanbuilder.G2BeanBuilder
    -port 1112
```

If you use this command-line option when using the wizard, then the port number you enter appears automatically in the G2 Connection Details panel, as described in [Specifying the Port](#).

## -class

Specifies the class for which you wish to create a Bean.

### To use the `-class` option:

```
→ java com.gensym.beanbuilder.G2BeanBuilder
    -class classname
```

where *classname* is the class from which to create a Bean. When specifying *classname* and not using the GUI, you must use all capital letters and include hyphens, unless the G2 class explicitly contains lower-case letters. When specifying the `-classes` command-line option, separate the class names with spaces. For example:

```
java com.gensym.beanbuilder.G2BeanBuilder
    -class MY-CLASS
```

If you use this command-line option when using the wizard, then the class name you enter appears automatically in the G2 Class Name panel, as described in [Entering the G2 Class](#).

If you are not using the graphical user interface, this option is required when launching the G2 Bean Builder, so that the utility knows which class to use to create the Bean.

## -force

Specifies whether to force an interface download. The default for this option is false.

**To use the `-force` option:**

```
➔ java com.gensym.beanbuilder.G2BeanBuilder
    -force
```

If you use this command-line option when using the wizard, then the force download checkbox is checked automatically when the G2 Class Name panel appears, as described in [Forcing an Interface Download](#).

## -iconfile

Specifies a 32x32 color image to represent the Bean when viewing it in an IDE. The default for this flag is `I32.gif`, which is located in the G2 JavaLink `beanbuilder.jar` file.

**To use the `-iconfile` option:**

```
➔ java com.gensym.beanbuilder.G2BeanBuilder
    -iconfile filename
```

where *filename* is the name of the image file to use for the Bean's icon. For example:

```
java com.gensym.beanbuilder.G2BeanBuilder
    -iconfile c:\images\myimage.gif
```

If you use this command-line option when using the wizard, then the file name you specify appears automatically in the Iconic Representation panel, as described in [Entering the File Name](#).

## -notg2icon

Specifies that the default icon to use to represent the Bean is `I32.gif`, located in the G2 JavaLink `beanbuilder.jar` file, or the image file specified by the `-iconfile` command-line option.

**To use the `-notg2icon` option:**

```
➔ java com.gensym.beanbuilder.G2BeanBuilder
    -notg2icon
```

If you use this command-line option when using the wizard, then the Use G2 icon for bean checkbox is set to false in the Iconic Representation panel, as described in [Entering the File Name](#).

## -dir

Specifies the JAR file home directory to use when generating the Bean. The default value is the path indicated by the value of the `com.gensym.class.user.repository` property with `\jars` appended. This property is defined in the JavaLink properties file, `.com.gensym.properties`.

### To use the `-dir` option:

```
→ java com.gensym.beanbuilder.G2BeanBuilder
   -dir directory
```

where *directory* is the path name to use for the JAR file. For example:

```
java com.gensym.beanbuilder.G2BeanBuilder
   -dir c:\jars\
```

If you use this command-line option when using the wizard, then the directory you specify appears automatically in the Bean Build Information panel, as described in [Entering the File Name](#).

## -jarfile

Specifies the JAR file name to use when generating the Bean. The default value is the name of the G2 class with `Bean.jar` appended to the name.

### To use the `-jarfile` option:

```
→ java com.gensym.beanbuilder.G2BeanBuilder
   -jarfile filename
```

where *filename* is the file name to use for the JAR file. For example:

```
java com.gensym.beanbuilder.G2BeanBuilder
   -jarfile MyBean.jar
```

If you use this command-line option when using the wizard, then the directory you specify appears automatically when the Bean Build Information panel appears, as described in [Entering the File Name](#).

## -activex

On Windows platforms only, specifies whether to generate an ActiveX component from the Bean. The default value is false.

### To use the `-activex` option:

```
→ java com.gensym.beanbuilder.G2BeanBuilder
   -activex
```

If you use this command-line option when using the wizard, then the Create ActiveX component from the bean? checkbox is checked automatically in the Active X Generation panel, as described in [Creating an ActiveX Component from the Bean](#).

## **-unreg**

On Windows platforms only, specifies whether to unregister an existing ActiveX control if it is already registered. The default value is false.

**To use the `-unreg` option:**

```
→ java com.gensym.beanbuilder.G2BeanBuilder  
    -activex -unreg
```

If you use this command-line option when using the wizard, then the Unreg existing class checkbox is checked automatically in the Active X Generation panel, as described in [Creating an ActiveX Component from the Bean](#).

## **+g**

Launches G2 Bean Builder with the graphical user interface wizard. When you launch G2 Bean Builder with no command-line option, you get the GUI, by default. When you launch it with the `-class` command-line option, you do not get the GUI, unless you use the `+g` command-line option.

## **+t**

Sets the trace output for the G2 Bean Builder utility to true. By default, tracing is not enabled. The trace output can provide information about problems encountered while downloading G2 classes.

## **+v**

Runs the G2 Bean Builder verification test. By default, the verification test is not run when you launch the utility. For more information, see [Checking the Installation](#).

# Using G2 Bean Builder Beans

---

*Describes how to use G2 Bean Builder beans as Java Beans and as ActiveX controls.*

Introduction **35**

Creating the G2 Class **36**

Creating the Bean **36**

Using the Bean in the Beans Development Kit (BDK) **37**

Using the Bean as an ActiveX Control in Visual Basic **48**



## Introduction

The G2 Bean Builder is a tool for extracting Java Beans from existing G2 class objects as JAR files and ActiveX controls.

This chapter illustrates the use of the JAR file by using Sun Microsystem's Beanbox, while it illustrates the use of the ActiveX control by using Microsoft's Visual Basic.

Neither of these examples is intended to be an in-depth guide to using third-party software. For full details on their use, please refer to the relevant product documentation.

## Creating the G2 Class

To illustrate the use of the G2 Bean Builder, first you must create a G2 object from which to generate the Bean. This example uses the test class detailed below because it has a variety of attribute types.

### To create a test G2 class:

- 1 In G2, create an object definition for the class `a-test-class` with the following class-specific attributes:
  - a-int is an integer, initially is 34;
  - a-float is a float, initially is 3.4e6;
  - a-text is a text, initially is "A TEST STRING";
  - a-symbol is a symbol, initially is hi-there;
  - a-truth-value is a truth-value, initially is false;
  - a-sequence is a sequence, initially is sequence (1, 2.3, the symbol fred, "This text belongs to this sequence", structure (fred: 1, ethal: "ethals structure text"));
  - a-structure is a structure, initially is structure (attone: the symbol hi-there, atttwo: "A Very complex object is this")
- 2 Create an instance of `a-test-class`.
- 3 Name that instance `a-test-class-instance`.

## Creating the Bean

The following instructions assume that the G2 Bean Builder is running on a Windows platform with Sun's Java Plug-in installed. The G2 Bean Builder automatically reconfigures itself on systems where ActiveX is not available so that ActiveX-related functions are not visible.

### To create the test Bean:

- 1 Start the G2 Bean Builder, using one of the following techniques:
  - ➔ Enter the following command at the command line:

```
java com.gensym.beanbuilder.G2BeanBuilder
```
  - ➔ From the Start menu, choose the following from your Gensym G2 program group:

```
G2 JavaLink > G2 Bean Builder
```
- 2 Configure the G2 Bean Builder to connect to your G2.  
For details, see [Configuring the G2 Connection Details](#).
- 3 Configure the class to download to be `A-TEST-CLASS`.

- 4 Accept the default icon representation.
- 5 Accept the default JAR file location.
- 6 Instruct the G2 Bean Builder to create an ActiveX component, as needed.
- 7 Continue with the G2 Bean Builder prompt to create the Bean.


The G2 Bean Builder creates a Java Bean called `ATestClassBean` found in `ATestClassBean.jar`. If an ActiveX component was created, it is registered as "ATestClassBean Bean Control."

## Using the Bean in the Beans Development Kit (BDK)

Sun Microsystem's Beans Development Kit (BDK) is a pure Java application, whose only dependency is the Java Development Kit (JDK) 1.2.1 or later. The BDK provides:

- Support for the JavaBeans APIs.
- A test container, called the "BeanBox," used to test Bean behavior.
- Sample Beans complete with their source code.
- The JavaBeans Specification.
- A tutorial.

This figure shows the BDK:



The above figure shows, from left to right:

- The ToolBox, a palette of beans.
- The BeanBox, an area for positioning beans and configuring their events.
- The property sheet, an area for configuring the properties of beans.

## Viewing the Bean in the Bean Box


To view the Bean in the Bean Box, you must load its associated JAR file.

### To view the Bean in the Bean Box:


- 1 In a command window, change to the BDK BeanBox product directory and enter this command:

```
run
```


The BDK BeanBox appears:



- 2 Choose LoadJar from the File menu on the main BeanBox composition window:



- 3 Use the dialog box to select and load `ATestClassBean.jar`.  
When loaded, the Bean is visible at the end of the ToolBox palette:




## Creating an Instance of the Bean

To create an instance of the Bean:

- 1 Click the ATestClassBean icon on the ToolBox palette.  
The cursor changes to a +.
- 2 Click anywhere in the BeanBox composition window to create the Bean.

This figure shows the two steps required to create an instance of the Bean:




In this figure, the ATestClassBean is surrounded by a box indicating that it is currently selected:



## Configuring the Bean

This figure shows the property sheet for ATestClassBean, which includes the SourceURL and G2ItemFetched properties, described below:



## The SourceURL Property

The SourceURL property specifies the G2 object that the selected Bean represents.

The URL references an existing G2 object resident in a G2 running on the indicated port of a specified machine. It takes the form:

```
g2://<host>:<portnumber>/<G2objectname>
```

For example:

```
g2://localhost:1111/A-TEST-CLASS-INSTANCE
```

## The G2ItemFetched Property

The G2ItemFetched property is a boolean flag to indicate that the Bean is to fetch the item specified by the SourceURL.

Assuming the SourceURL is set to a valid G2 object, setting the flag to true causes the Bean to connect to the specified G2 and probe the indicated object to obtain all of its properties, which are defined in the class-specific attributes of the object class definition.

---

**Note** G2 must be running for the item to be fetched.

---

The property sheet displays only properties of certain types, for example, *String*, *int*, *float*. For more information, see the BDK user documentation from Sun.

For this reason, the definition of the G2 attributes determines whether or not the corresponding Bean property appears in the property sheet. You must define the G2 attribute properly for it to appear in the property sheet.

For example, the following G2 attribute definition makes the property accessible from the BDK's BeanBox property sheet as a boolean:

```
g2-item-fetched is a truth-value, initially is false
```

The following G2 attribute definition, exported as an object because this G2 attribute accepts any type or item, creates a Java Object rather than a native type, so it does not appear in the property sheet:

```
x-offset initially is 23
```

To access this property via the property sheet, it should be redefined to be "strongly" typed as an integer. G2 can then export the definition for this attribute as a Java *int* rather than as a generic object.

For example:


```
x-offset is an integer, initially is 23
```

---

**Note** When a G2 class definition is changed, it should be reexported to Java, using the G2 Bean Builder or G2 DownloadInterfaces utilities, to ensure that the new definition is available to Java.


---

Once a correct SourceURL is specified and G2ItemFetched is set to true, then the exported Bean connects to **a-test-class-instance** in the G2 at `localhost:1111`. Reselecting **ATestClassBean** in the BeanBox automatically displays the current values of the exported attributes of **a-test-class-instance**, as follows:



At this point the Bean is “aware” of its specified G2 object and vice versa, as this figure shows:

A-TEST-CLASS-INSTANCE, an a-test-class	
Notes	OK
Names	A-TEST-CLASS-INSTANCE
A int	2456
A float	3.456
A text	"A TEST G A THING"
A symbol	hi-there
A thruth value	false
A sequence	sequence (1, 2,3, the symbol fred, "This text belongs to this sequence", structure (fred: 1, ethal: "ethals structure text"))
A structure	structure (attone: the symbol hi-there, atttwo: "A Very complex object is this")





A-TEST-CLASS-INSTANCE

A-TEST-CLASS



If you change an attribute value of the G2 object, the change appears in the property sheet of the Bean and vice versa.

---

**Note** It is necessary to reselect ATestClassBean in the BeanBox window for the property sheet to be updated when attributes are changed in G2.

---

### The EnableUIForMessages Property

The EnableUIForMessage boolean property controls whether or not the Bean reports exceptions to the user via a GUI dialog box. Some IDE’s such as Visual Basic do not catch and report exceptions. In such environments, an exception may at best go unreported, or in the worst case hang the system. Java IDE’s tend to catch and report exceptions. If this property is set to true and the IDE supports it, then the Bean causes the display of a dialog box containing the exception message, as well as throwing the exception.

### The UseG2Icon Property

The UseG2Icon boolean property controls whether or not the icon displayed by the Bean is the same as the G2 icon for the item specified by SourceURL or is the image that was specified as the Beans icon during the construction of the Bean.

## The ScaleImageToFit Property

The ScaleImageToFit boolean property controls whether or not the icon image for the Bean, as controlled by the UseG2Icon property, is scaled to fit within the bounds of the Bean. If set to true, the image is scaled in size so it fits within the bounds of the Bean. If set to false and the UseG2Icon property is true, then the image is displayed within the bounds of the Bean starting at 0,0 (top left). If the UseG2Icon property is set false, the image is displayed centrally within the bounds of the Bean. If the image is larger than the bounds of the Bean, it is cropped.

## The ShowIconUpdates Property

The ShowIconUpdates boolean property controls whether or not the icon of the Bean reflects changes that take place in the G2 icon for the specified item.


---

**Note** This property is applicable only if the UseG2Icon property has been set to true and Telewindows2 Toolkit has been installed.


---

## Interacting with Other Beans


The following figure shows the BeanBox composition window with a BlueButton added from the Toolbox palette and the actionPerformed button push event has been selected from the Edit menu:



Here the action is being “tied to” the test Bean:



When the two Beans are connected, the EventTargetDialog window appears and displays the available methods of the test Bean:




Events for the object defined in G2 are also available in Java and so appear in this list. For more information, see the chapter on writing G2 Bean events in the *G2 JavaLink User's Guide*.

Selecting one of these events causes the selected method to be called when the button is pressed.

For a detailed example, see the BDK tutorial supplied with BDK1.1.

# Using the Bean as an ActiveX Control in Visual Basic

The following figure shows a Visual Basic 5.0 project:



The palette on the left holds a number of standard Visual Basic controls.

## Importing Beans into Visual Basic

To use the Bean as an ActiveX control, you import the Bean as a custom control into Visual Basic.

**To import the Bean as an ActiveX control into Visual Basic:**

- 1 From Visual Basic, choose Components from the Project menu:
- 2 Select ATestClassBean Bean Control.
- 3 Accept the dialog.

After importing the component, ATestClassBean appears on the Toolbox, as follows:




You can work with the imported Bean in the same way as you would with any other ActiveX component.

## Creating an Instance of the ActiveX Control

**To create an instance of the ActiveX control:**

- 1 Click the ATestClassBean icon in the Toolbox.  
The cursor changes to a + when positioned over the form.
- 2 Draw a box on the Form to create an instances of the control.

This figure shows the two steps required to create an instance of the control:




If Visual Basic reports that the generated G2 ActiveX Bean control has not been registered, when a user attempts to create and draw the control on a VB form, the most likely cause is that the file `beans.ocx` is not found.

---

**Note** The Packager uses a common control file called `beans.ocx` that is normally placed in `c:\Program Files\JavaSoft\JRE\1.3\bin\`, assuming the Java Plug-in is installed at `c:\Program Files\JavaSoft\JRE\1.3\`. This file must be copied to any ActiveX directory created by the G2 Bean Builder, or the generated ActiveX controls fail to function.

---

This figure shows A-TEST-CLASS Bean on the Form and its properties as displayed in the Properties window:



For information about configuring the properties of the Bean, see [Configuring the Bean](#).



@ A B C D E F G H I J K L M  
# N O P Q R S T U V W X Y Z

---

**A**

About button  
Active X Generation panel  
ActiveX  
    *See Also* ActiveX controls  
    Packager  
-activex command-line option  
ActiveX controls  
    building from Java Beans  
    configuring properties of  
    creating instances of in Visual Basic  
    generating  
        using command-line option  
        using wizard  
    location of  
    unregistering  
        using command-line option  
        using wizard  
    viewing Java Beans in Visual Basic  
asynchronous signals  
attributes  
    accessing for Java Beans  
    defining G2 class-specific  
    strongly typed

**B**

Back button  
Bean Build Information panel  
beaninfo file  
Beans  
    *See* Java Beans  
Beans Development Kit (BDK)  
    troubleshooting, using  
    using  
beans.ocx file  
    copying to `activex` directory  
    using with Packager  
bounds checking  
buttons  
    About  
    Back

Exit  
Next  
Restart

**C**

-class command-line option  
Class field  
classes  
    creating G2  
    downloading data for  
    specifying G2  
        using command-line option  
        using wizard  
CLASSPATH environment variable  
    using with BDK  
    using with Java Plug-in  
class-specific attributes, defining G2  
color images  
    .com.gensym.properties file  
command for running G2 Bean Builder  
    with a GUI  
command-line options  
    +g  
    +t  
    +v  
    -activex  
    -class  
    -dir  
    -force  
    -host  
    -iconfile  
    introduction to  
    -jarfile  
    -notg2icon  
    -port  
    -unreg  
commands  
    for running G2 DownloadInterfaces  
        without a GUI  
connecting to G2  
connection to G2, configuring  
    using command-line option  
    using wizard

Create ActiveX component from the bean?  
checkbox  
customer support services

## D

`-dir` command-line option  
Dir field  
directory, configuring for JAR files  
distributing Java Beans  
downloading  
    class data  
    interfaces  
        configuring G2 class  
        forcing

## E

EnableUIForMessages property  
events, definition of  
Exit button

## F

File name field  
files  
    configuring  
        for image files  
        for JAR files  
    location of generated  
Finished panel  
`-force` command-line option  
forcing interface download  
    using command-line option  
    using wizard

## G

`+g` command-line option  
G2  
    class  
        creating  
        specifying  
    configuring connection to  
    connecting to  
    differences with Java  
    host  
    icons  
    Java Beans

mapping classes to Java interfaces  
port  
G2 Bean Builder  
    command-line options for  
    installing  
    introduction to  
    running  
        requirements for  
        with GUI  
        wizard  
    using Beans created from  
G2 Class Name panel  
G2 Connection Details panel  
G2 DownloadInterfaces  
    running  
        without GUI  
`g2evlis.kb` file  
G2ItemFetched property  
getters  
graphics  
    *See* icons  
GUI  
    command-line option for launching  
        without  
    running G2 Bean Builder  
        with  
    running G2 DownloadInterfaces  
        without

## H

`-host` command-line option  
Host field  
host, specifying  
    using command-line option  
    using wizard

## I

`-iconfile` command-line option  
Iconic Representation panel  
icons  
    specifying  
        not to use G2  
        using command-line option  
        using G2 icon  
        using image files  
IDEs  
    dithering images in  
    reporting exceptions in

- viewing Beans in images
  - See* icons
- installation
  - checking
  - G2 Bean Builder
  - software requirements for
  - troubleshooting

## J

- JAR files
  - creating
  - specifying
    - using command-line option
    - using wizard
  - specifying directory
    - using command-line option
    - using wizard
  - `-jarfile` command-line option
- Java
  - differences with G2
  - event model
  - inheritance model
  - interfaces, mapping G2 classes to
- Java Beans
  - accessing attributes of
  - building
  - configuring properties of
    - in Bean Box
    - in Visual Basic
  - creating instances of
    - in Bean Box
    - in Visual Basic
  - creating sample
  - definition of
  - distributing, requirements for
  - events
  - G2
  - interacting with other Beans
  - using
  - viewing
    - in Bean Box
    - in Visual Basic
- Java Development Kit (JDK)
- Java Plug-in
  - Packager
- Java Runtime Environment (JRE)

## L

- listeners

## M

- monochrome images
- multiple inheritance

## N

- Next button
- `-notg2icon` command-line option

## P

- Packager, ActiveX
- plug-and-play
  - `-port` command-line option
- Port field
- port, specifying
  - using command-line option
  - using wizard
- Progress of Bean Building panel
- property sheet
  - viewing
    - in Bean Box

## R

- `readme` file
- REG files
  - editing
- registry files
  - See* REG files
- requirements, software
- Restart button

## S

- ScaleImageToFit property
- setters
- ShowIconUpdates property
- software requirements
- source objects
- SourceURL property
- strongly typed attributes
- Summary panel

## T

- +t command-line option
- target objects
- TCP/IP port
- tracing, command-line option for

## U

- unreg command-line option
- Unreg existing class checkbox
- Use G2 icon for bean checkbox
- UseG2Icon property

## V

- +v command-line option
  - checking installation, using
  - using
- Visual Basic
  - importing Beans into
  - viewing Java Beans as ActiveX controls in

## W

- Welcome panel
- wizard, running